



ENDURO SPIRAL HOSE

WITH SUPERTUFF (ST)
MSHA COVER



Hydraulink[®]

Hose Solutions

ENDURO
DN 19 3/4" WP 350 BAR 5510 PSI ISO 18752-CC EXCEEDS PERFORMANCE SAE100 R15 MSHA
ENDURO
DN 25 1" WP 420 BAR 6090 PSI ISO 18752-CC EXCEEDS PERFORMANCE SAE100 R15 MSHA

ENDURO SPIRAL HOSE

Hydraulink are pleased to introduce our new **ENDURO spiral hose** range.

ENDURO spiral is an extremely flexible slim profile hose featuring our very high wear and abrasion resistant SuperTuff (ST) MSHA cover for increased protection against abrasion in severe operating environments.

The new **ENDURO** hoses have been specifically developed for demanding applications and are an ideal choice for applications in **Mining, Forestry, Earthmoving** and **Construction**.

ENDURO hoses are designed to increase service life, lower maintenance costs, and reduce downtime - without loss of flexibility or bend radius.

**TESTED TO 1 MILLION
IMPULSE CYCLES**

ENDURO 5000

ENDURO 6000



ENDURO5000-12 Hydraulink

ENDURO


ENDURO6000-16 Hydraulink

ENDURO


SPECIFICATIONS

- NBR Tube compatible with mineral oil-based hydraulic fluids and bio-degradable hydraulic fluids.
- SuperTuff (ST) cover exceeds ISO standard abrasion resistance requirements by 10 times.
- MSHA cover meets Flame Resistance and Antistatic specifications of ISO 6805/ MDG41/ RS23 for mining applications.
- Exceeds ISO 18752 – CC, SAE 100R13/R15.
- Flexible up to 1/2 SAE minimum bend radius.
- Impulse tested up to 1 million cycles.
- Four spiral wire construction for Enduro 5000 up to -24 size and Enduro 6000 up to -20 size.
- Six spiral wire construction for Enduro 5000 -32 and Enduro 6000 -24.

ENDURO5000-06 **Hydraulink** **ENDURO** DN 10 3/8" WP 380 BAR 5510 PSI ISO 18752-CC MSHA

HOSE TYPE	ENDURO 5000 EXCEEDS ISO 18752 – CC/SAE 100R13								
Dash Size	-6	-8	-10	-12	-16	-20	-24	-32	
OD (mm)	20.2	22.9	26.5	30.5	37.9	45.9	53.4	71.5	
BR (mm)	65	90	100	120	150	210	250	540	
MWP (bar/psi)	380/5510	380/5510	380/5510	380/5510	350/5075	350/5075	350/5075	350/5075	
Wire Layers	4	4	4	4	4	4	4	6	

ENDURO6000-06 **Hydraulink** **ENDURO** DN 10 3/8" WP 420 BAR 6090 PSI ISO 18752-CC EXCEEDS SAE100 R15 MSHA

HOSE TYPE	ENDURO 6000 EXCEEDS ISO 18752 – CC/SAE 100R15							
Dash Size	-6	-8	-10	-12	-16	-20	-24	
OD (mm)	20.2	22.9	26.5	30.5	37.5	47.3	57.4	
BR (mm)	65	90	100	120	150	400	460	
MWP (bar/psi)	420/6100	420/6100	420/6100	420/6100	420/6100	420/6100	420/6100	
Wire Layers	4	4	4	4	4	4	6	

DN 19 3/4" WP 360 BAR 5510 PSI ISO 18752-CC EXCEEDS PERFORMANCE SAE100 R13 MSHA

DN 25 1" WP 420 BAR 6090 PSI ISO 18752-CC EXCEEDS SAE100 R15 MSHA

Hydraulink[®]

Best under pressure

AUSTRALIA HEAD OFFICE

Hydraulink Australia Pty Limited
123 Long St
Smithfield
NSW 2164
P +61 2 8785 4600
F +61 2 8785 4626
1300 36 37 34
hydraulink.com.au

NEW ZEALAND HEAD OFFICE

Hydraulink Fluid Connectors Ltd
21 O'Rorke Road
Penrose
Auckland 1061
P +64 9 525 2626
F +64 9 525 2151
0800 80 66 66
hydraulink.com

INDONESIA HEAD OFFICE

Hydraulink Indonesia
World Trade Center 5
Building 3Ath Floor,
Jl. Jend Sudirman Kav 29-31
Jakarta 12920
Indonesia
P +62 21 2598 5017
hydraulink.com.au

**HYDRAULINK HAS OVER 400 SERVICE CENTRE POINTS
ACROSS NEW ZEALAND, AUSTRALIA, AND THE ASIA PACIFIC.**

Visit www.hydraulink.com to find your nearest dealer.