

EXTREMELY HIGH PRESSURE HOSE

EFG6K

FOUR/SIX SPIRAL WIRE HOSE

SPIRAL WIRE REINFORCED HOSE - SAE 100R15



- Due to manufacturing tolerances, external dimension is an average.
- Recommended for: Extremely high pressure and high impulse hydraulic applications.
- Internal tube: -6, -8, -10, -12, -16, -20: Nitrile based; -24: Neoprene based.
- Reinforcement: Four (six for -20, -24) alternating layers of spiralled, high tensile steel wire.
- External cover: Neoprene based, MSHA approved.
- Temperature range: -40°C to +121°C
- Standards: SAE 100R15. Meets or exceeds performance requirements of EN 856 4SP (-8) and EN 856 4SH (-12, -16)
- Characteristics: Extremely flexible. Compatible with biodegradable hydraulic fluids like synthetic esters, polyglycols and vegetable oils and petroleum-based fluids in sizes -06 to -20 (not -24)
- Optional: EFG6K-MTF: the range of EFG6K is also available with the Gates special MegaTuff™ cover which offers 300 times the abrasion resistance of the standard cover as per ISO 6945, superior ozone/weathering resistance - please contact Hydraulink for further details and availability.

Part Number	Internal Size	Internal DN	Internal Diameter (in)	External Diameter (mm)	Working Pressure (psi)	Working pressure (bar)	Min burst pressure (psi)	Min burst pressure (bar)	Min bend radius (mm)
6EFG6K	06	10	3/8	20.5	6000	420	24000	1680	65
8EFG6K	08	12	1/2	24.0	6000	420	24000	1680	90
10EFG6K	10	16	5/8	27.6	6000	420	24000	1680	100
12EFG6K	12	19	3/4	31.4	6000	420	24000	1680	120
16EFG6K	16	25	1	38.7	6000	420	24000	1680	150
20EFG6K	20	31	1.1/4	50.0	6000	420	24000	1680	210
24EFG6K	24	38	1.1/2	57.4	6000	420	24000	1680	250
32EFG6K	32	51	2	71.1	6000	420	24000	1680	635