

## MEDIUM PRESSURE HOSE

### ACR

HIGH TEMP. OIL/AIR RETURN  
BRAIDED WIRE REINFORCED HOSE - FABRIC  
COVER



- Due to manufacturing tolerances, the external dimension is an average.
- For -24 and 32 sizes please see alternative ACP series.
- Recommended for: Pressurised hot oil return lines and air compressor lines, power steering, tilt cab cylinders, engine and transmission coolant and filtration lines.
- Internal tube: CPE based.
- Reinforcement: One braid of high tensile steel wire.
- External cover: Oil resistant textile braid, impregnated with synthetic rubber. MSHA approved.
- Temperature range: -40°C to +150°C. Phosphate ester fluids: -40°C to +100°C.
- Air: -40°C to +121°C.
- Vacuum range: To 30In.Hg (760mm.Hg)
- Standards: Gates proprietary. Meets the requirements of SAE J1019 performance specifications for use in high temperature transmission oil systems and high temperature lubrication oil systems using petroleum based oils.
- Characteristics: Very good resistance to weathering and ozone. ACR hose is compatible with a variety of fluids such as hydraulic oil, phosphate esters.

Part Number	Internal Size	Internal DN	Internal Diameter (in)	External Diameter (mm)	Working Pressure (psi)	Working pressure (bar)	Min burst pressure (psi)	Min burst pressure (bar)	Min bend radius (mm)
24ACR500	24	38	1.1/2	49.5	500	35	2000	140	380
32ACR500	32	51	2	63.0	500	35	2000	140	460
40ACR500	40	63	2.1/2	75.4	500	35	2000	140	560
48ACR500	48	76	3	88.9	500	35	2000	140	610