

LOW PRESSURE HOSE

LOL

PUSH-LOCK FIBRE BRAID HOSE BRAIDED FIBRE REINFORCED HOSE



- Due to manufacturing tolerances, the external dimension is an average.
- Recommended for: Petroleum-based hydraulic oils, antifreeze solutions, water, hot lubricating oils and air. Suitable for low-pressure cleaning and pneumatic systems, return lines and low pressure lines. Push-Lock hose and couplings are not recommended for pressure surge applications or critical applications.
- Internal tube: Nitrile based.
- Reinforcement: One fibre braid.
- External cover: Oil and abrasion resistant synthetic rubber (blended nitrile). MSHA approved.
- Temperature range: -40°C to +100°C constant and +121°C intermittent.
- Standards: Gates proprietary.
- Characteristics: Available in 6 colours for easy colour coding. Easy to assemble.
- Suffix A = black, B = blue, C = grey, G = green, R = red, Y = yellow. Please note some size/colour combinations are not held in inventory and are subject to minimum order requirements.

Part Number	Colour	Internal Size	Internal Diameter (in)	External Diameter (mm)	Working Pressure (psi)	Working pressure (bar)	Min burst pressure (psi)	Min burst pressure (bar)	Min bend radius (mm)
3LOLA	Black	03	3/16	10.4	300	21	1200	84	75
4LOLA	Black	04	1/4	11.9	300	21	1200	84	75
5LOLA	Black	05	5/16	14.0	300	21	1200	84	75
6LOLA	Black	06	3/8	15.9	300	21	1200	84	75
8LOLA	Black	08	1/2	19.6	300	21	1200	84	130
10LOLA	Black	10	5/8	23.9	300	21	1200	84	150
12LOLA	Black	12	3/4	26.9	300	21	1200	84	180