


STANDARD SERIES

QANV


POPPET SEAL COUPLINGS

INTERCHANGE ACCORDING TO ISO 7241-1 PART A

- Please enquire for other combinations of base size and thread form.
- Overall length when connected is calculated based on both couplings having the same thread form and size.
- Recommended for: Agricultural applications.
- Connection: Connect without pressure - pull back female sleeve and push couplings to connect. Disconnect under pressure not allowed - pull back female sleeve to disconnect.
- Latching: Balls latching.
- Shut-off system: Poppet valve. Guidevalve with mechanical backstop.
- Temperature range: -25°C to +125°C
- Standards: Interchangeability according to ISO 7241-1 part A



F



M

Part Number	Base Size	Threadform	Thread size	Coupling Length - L1	Coupling O.D - D1	Hex Size A/F (Hex 1)	Inner Coupling O.D - D3
QANV-F04	04	BSPPF socket	1/4-19	47.2	25	49	
QANV-F06	06	BSPPF socket	3/8-19	57.0	32	22	
QANV-F12	12	BSPPF socket	3/4-14	82.5	48	34	
QANV-F16	16	BSPPF socket	1-11	100.0	56	41	
QANV-M04	04	BSPPF socket	1/4-19	38.6	21	24	11.8
QANV-M06	06	BSPPF socket	3/8-19	39.0	24	32	17.2
QANV-M12	12	BSPPF socket	3/4-14	55.0	38	34	29
QANV-M16	16	BSPPF socket	1-11	66.0	45	34	34.3