Hydraulink®

MULTIPURPOSE HOSE

TERMINATOR

Terminator MULTI-PURPOSE HOSE
CORD REINFORCED INDUSTRIAL HOSE



- Recommended for: Terminator is one tough hose with a rugged cover for outstanding abrasion resistant capability and extended service life where constant flexing and bending is required. This top-of-the-line industrial and oil-resistant hose is designed for applications involving air/oil/water transfer as well as grease sprays/paraffin waxes/salt solutions and a variety of chemicals. It offers excellent durability for extra long life in mining/air drill/construction/poultry plants/quarries/shipyards/food processing/ railroads and other severe service environments. Excellent industrial hose with weather and ozone resistance; Nonconductive at 1000 volts D.C.
- Temperature range:-40°F to +212°F (-40°C to +100°C) continuous service.
- Tube: Type C (Nitrile) hose. Black. RMA (Class A) high oil resistance.
- Reinforcement: Synthetic high tensile cord.
- Cover: Type C4 (Carboxylated Nitrile). Yellow. RMA (Class A) high oil resistance.

Part Number	Internal Size	Internal Size (mm)	External Diameter (mm)	Working Pressure (psi)	Working pressure (bar)	Min burst pressure (psi)	Max suction pressure - (mm Hg)	Min bend radius (mm)
TERMINATOR-04	04	6.4	14.5	501	35	750	762	76
TERMINATOR-06	06	9.5	19.1	501	35	750	635	76
TERMINATOR-08	08	12.7	22.6	501	35	750	635	127
TERMINATOR-12	12	19.1	31	501	35	30	381	152
TERMINATOR-16	16	25.4	38.4	501	35	30	254	203

Please contact Hydraulink for further details and availability. Hydraulink reserve the right to change technical specifications without notice.