


STANDARD SERIES

QNV - TECHNICAL DATA
 POPPET SEAL COUPLINGS
 INTERCHANGE WITH ISO 7241-1 PART A IN 08 SIZE



Part Number	Rated Flow (l/min)	Force to connect - N	Force to connect - lb	Maximum WP Connected - bar	Maximum WP Connected - psi	Minimum BP Disconnected - psi	Minimum BP Connected - psi	Fluid Spill - ml max
QNV-F04	15	55	12.1	350	5000	20000	20000	0.8
QNV-F06	50	85	18.7	300	4500	20000	17400	1.3
QNV-F08	75	80	17.9	300	4500	17400	17400	1.8
QNV-F0812Q	75	80	17.9	300	4500	17400	17400	1.8
QNV-F0814Q	75	80	17.9	300	4500	17400	17400	1.8
QNV-F12	150	150	33.7	300	4500	17400	17400	8
QNV-F16	220	130	28.6	250	3625	14500	14500	13
QNV-F20	340	145	31.9	220	3300	13500	13500	30
QNV-F24	450	265	58.4	200	3000	12000	12000	34
QNV-F32	1000	250	56.2	150	2250	9000	9000	100
QNV-M04	15	55	12.1	350	5000	20000	20000	0.8
QNV-M06	50	85	18.7	300	4500	17400	17400	1.3
QNV-M08	75	80	17.9	300	4500	17400	17400	1.8
QNV-M0812Q	75	80	17.9	300	4500	17400	17400	1.8
QNV-M0814Q	75	80	17.9	300	4500	17400	17400	1.8
QNV-M12	150	150	33.7	300	4500	17400	17400	8
QNV-M16	220	130	28.6	250	3625	14500	14500	13
QNV-M20	340	145	31.9	220	3300	13500	13500	30
QNV-M24	450	265	58.4	200	3000	12000	12000	34
QNV-M32	1000	250	56.2	150	2250	9000	9000	100