
Hydraulink®

STANDARD SERIES

QNS

BALL SEAL COUPLINGS
INTERCHANGE WITH ISO 7241-1 PART A IN 08 SIZE



- Please enquire for other thread forms and sizes. For sizes larger than 16 (1) refer to QNV series.
- NOTE: Only size 08 (1/2) is interchangeable with ISO 7241-1 part A.
- Recommended for: Agriculture, industrial, construction, earthmoving.
- Connection: Connect without pressure - pull back female sleeve and push couplings to connect. Disconnect under pressure not allowed - pull back female sleeve to disconnect.
- Latching: Balls latching.
- Shut-off system: Ball valve.
- Temperature range: -25°C to +125°C
- Standards: 08 (1/2) size only; Interchangeability according to ISO 7241-1 part A
- All other sizes; Interchangeability according to Faster internal standard. Interchangeability with all QNV series couplings (all sizes).

Part Number	Base Size	Threadform	Thread Size	Coupling Length - L1	Coupling O.D - D1	Hex Size A/F (Hex 1)	Inner Coupling O.D - D3
QNS-F04	04	BSPPF socket	1/4-19	50.0	27	19	
QNS-F06	06	BSPPF socket	3/8-19	59.5	33	24	
QNS-F08	08	BSPPF socket	1/2-14	68.0	38	27	
QNS-F12	12	BSPPF socket	3/4-14	82.5	48	34	
QNS-F16	16	BSPPF socket	1-11	100.0	56	41	
QNS-M04	04	BSPPF socket	1/4-19	33.0	21	19	14.1
QNS-M06	06	BSPPF socket	3/8-19	39.0	27	24	18.9
QNS-M08	08	BSPPF socket	1/2-14	46.0	30	27	20.5
QNS-M12	12	BSPPF socket	3/4-14	53.5	38	34	27.9
QNS-M16	16	BSPPF socket	1-11	66.0	45	41	31.3

Please contact Hydraulink for further details and availability. Hydraulink reserve the right to change technical specifications without notice.