Hydraulink®


STANDARD SERIES

QNS - TECHNICAL DATA

BALL SEAL COUPLINGS

INTERCHANGE WITH ISO 7241-1 PART A IN 08 SIZE

Pressure Drop



Part Number	Rated Flow (l/min)	Force to connect - N	Force to connect - lb	Maximum WP Connected - bar	Maximum WP Connected - psi	Minimum BP Disconnected - psi	Minimum BP Connected - psi	Fluid Spill - ml max
QNS-F04	15	55	12.1	250	3625	14500	20300	0.7
QNS-F06	30	83	18.3	250	3625	14500	20300	1
QNS-F08	50	89	19.6	200	2900	11600	17400	1.5
QNS-F12	80	170	37.4	170	2465	13775	21750	7
QNS-F16	140	140	30.8	220	3190	17400	23200	11
QNS-M04	15	55	12.1	250	3625	14500	20300	0.7
QNS-M06	30	83	18.3	250	3625	14500	20300	1
QNS-M08	50	89	19.6	200	2900	12325	17400	1.5
QNS-M12	80	170	37.4	170	2465	9860	21750	7
QNS-M16	140	140	30.8	220	3190	13050	23200	11

Please contact Hydraulink for further details and availability. Hydraulink reserve the right to change technical specifications without notice.