
Hydraulink®

STANDARD SERIES

QHNV - TECHNICAL DATA

POPPET SEAL COUPLINGS
INTERCHANGE ACCORDING TO ISO 7241-1 PART B



Part Number	Rated Flow (l/min)	Force to connect - N	Force to connect - lb	Maximum WP Connected - bar	Maximum WP Connected - psi	Minimum BP Disconnected - psi	Minimum BP Connected - psi	Fluid Spill - ml max
QHNV-F04	17	65	14.3	450	6750	27000	30000	1
QHNV-F06	50	80	17.6	300	4500	19500	18000	1.5
QHNV-F08	75	92	20.3	350	5250	21000	21000	2.8
QHNV-F12	190	120	26.4	250	3625	16500	14500	10
QHNV-F16	270	180	39.6	300	4500	18000	18000	13
QHNV-M04	17	65	14.3	450	6750	27000	30000	1
QHNV-M06	50	80	17.6	300	4500	27000	18000	1.5
QHNV-M08	75	92	20.3	350	5250	22500	21000	2.8
QHNV-M12	190	120	26.4	250	3625	14500	14500	10
QHNV-M16	270	180	39.6	300	4500	18000	18000	13

Please contact Hydraulink for further details and availability. Hydraulink reserve the right to change technical specifications without notice.