
Hydraulink®

SCREW LOCK SERIES

QPVV

HYDRAULIC TOOL COUPLINGS
INTERCHANGE WITH EUROPE AND US MARKETS



- QPVV series are only available in base sizes 04 and 06 (1/4 and 3/8).
- Please enquire for further thread forms and sizes.
- Connection: Connect with pressure - screw couplings together to connect.
- Disconnect with pressure - unscrew couplings to disconnect.
- NOTE: Can be connected with pressure in either or both couplings.
- Latching: Threaded with safety lock.
- Shut-off system: Poppet valve. Interchanges with ball-type hydraulic tool couplings.
- Temperature range: -25°C to +125°C
- Standards: Faster proprietary standard; interchange with US and European hydraulic tool couplings.

Part Number	Base Size	Threadform	Thread Size	Coupling Length - L1	Coupling O.D - D1	Hex Size A/F (Hex 1)
QPVV-F04L	04	NPTF male boss	1/4-18	63	33	21
QPVV-F06L	06	NPTF male boss	3/8 - 18	83	36	25
QPVV-M04AC	04	NPTFF socket	1/4-18	63	30	27
QPVV-M06AC	06	NPTFF socket	3/8-18	83	35	32

Please contact Hydraulink for further details and availability. Hydraulink reserve the right to change technical specifications without notice.