Hydraulink

SLIMLINE WIRE BRAID HOSE

H16

R16 TWO WIRE BRAID HOSE
BRAIDED WIRE REINFORCED HOSE - SAE 100R16



- Due to manufacturing tolerances, the external dimension is an average.
- Recommended for: medium pressure hydraulic applications.
- Suitable for: Mineral & vegetable oils, water-based solutions, water, air & inert gases.
- Internal tube: Synthetic rubber.
- Reinforcement: Two high-tensile steel braids.
- External cover: H.A.R.C weather & high abrasion resistance synthetic rubber. MSHA approved.
- Temperature range: -40°C to 100°C (125°C discontinuous)
- Standards: Meets or exceeds SAE 100R16, EN857 2SC.
- Characteristics: Compact construction, extra flexible.

Part Number	Internal Size	Internal Diameter - DN	Internal Diameter - inches	External Diameter - mm	Working Pressure - psi	Working pressure - bar	Min burst pressure - psi	Min burst pressure - bar	Min bend radius - mm
H16-04ST	04	6	1/4	13.2	6100	420	24400	1680	45
H16-06ST	06	10	3/8	16.7	5100	350	20400	1400	65
H16-08ST	08	12	1/2	20.1	5100	350	20400	1400	90

Please contact Hydraulink for further details and availability. Hydraulink reserve the right to change technical specifications without notice.