

HIGH TEMPERATURE HOSE

H2CXT

HIGH TEMP TWO WIRE BRAID HOSE
FAHRENHEIT HIGH TEMP - BRAIDED WIRE
REINFORCED HOSE - EN 857 2SC



- Due to manufacturing tolerances, the external dimension is an average.
- Recommended for: High to medium pressure hydraulic applications.
- Suitable for: Mineral & vegetable oils, diesel, water-based solutions, water, air & inert gases.
- Internal tube: Synthetic rubber.
- Reinforcement: Two high tensile steel wire braids.
- External cover: Weather & abrasion resistant synthetic rubber. MSHA approved.
- Temperature range: -40°C to +135°C constant (150°C discontinuous). Air not higher than 121°C
- Standards: EN 857 2SC, SAE J30

Part Number	Internal Size	Internal Diameter - DN	Internal Diameter - Inches	External Diameter - mm	Working Pressure - psi	Working pressure - bar	Min burst pressure - psi	Min burst pressure - bar	Min bend radius - mm
H2CXT-04	04	6	1/4	13.4	5800	400	23200	1600	50
H2CXT-06	06	10	3/8	17.3	4800	330	19200	1320	65
H2CXT-08	08	12	1/2	20.5	4000	275	16000	1100	90
H2CXT-10	10	16	5/8	24.2	3600	250	14400	1000	100
H2CXT-12	12	19	3/4	27.8	3100	215	12400	860	120
H2CXT-16	16	25	1	34.7	2400	165	9600	660	150
H2CXT-20	20	32	1 1/4	43.3	1800	125	7200	500	210
H2CXT-24	24	38	1 1/2	49.6	1300	90	5200	360	300
D2XT-32	32	51	2	67	1150	80	4600	320	630