Hydraulink®

JACKING HOSE

DSJ

TWO WIRE BRAID JACKING HOSE
BRAIDED WIRE REINFORCED JACK HOSE



- Due to manufacturing tolerances, the external dimension is an average.
- Static (non-impulse) pressure rating for hydraulic jack applications only, reduced safety factor (2:1)
- Recommended for: Hydraulic jack applications.
- Suitable for: Mineral & vegetable oils.
- Internal tube: Synthetic rubber.
- Reinforcement: Two high-tensile steel braids.
- External cover: Weather & high abrasion resistance synthetic rubber. MSHA approved.
- Temperature range: -40°C to +100°C (150°C discontinuous)
- Standards: Proprietary. (Meets performance requirements of former IJ100 standard)
- Characteristics: Compact construction.

Part Number	Internal Size	Internal Diameter - DN	Internal Diameter - inches	External Diameter - mm	Working Pressure - psi	Working pressure - bar	Min burst pressure - psi	Min burst pressure - bar	Min bend radius - mm
DSJ-04	04	6	1/4	13.3	10000	700	20000	1400	50
DSJ-06	06	10	3/8	17.3	10000	700	20000	1400	65

Please contact Hydraulink for further details and availability. Hydraulink reserve the right to change technical specifications without notice.