

## ENDURO MULTISPIRAL HOSE

### ENDURO4000

ENDURO ST COVER - FOUR/SIX SPIRAL WIRE HOSE  
SPIRALLED WIRE REINFORCED HOSE - SAE 100  
R12 - MILLION IMPULSE CYCLES



- Comes with SuperTuff (ST) cover for increased protection against abrasion in severe operating environments
- Recommended for: Extremely high pressure and high impulse hydraulic applications.
- Internal tube: Synthetic rubber, resistant against hydraulic fluids (HL, HLP, HLPD, HVLP, HFA, HFAS, HFB, HFC) and bio-degradable hydraulic fluids.
- Reinforcement: Four alternating layers of spiralled, high tensile steel wires.
- External cover: Weather & abrasion resistant synthetic rubber. MSHA approved.
- Temperature range: -40°C to +121°C
- Standards: ISO 18752-CC Exceeds SAE 100 R12.
- Characteristics: Extra flexible, up to 1/2 SAE bend radius

Part Number	Internal Size	Internal Diameter - DN	Internal Diameter - Inches	External Diameter - mm	Working Pressure - psi	Working pressure - bar	Min burst pressure - psi	Min burst pressure - bar	Min bend radius - mm
ENDURO40 00-32	32	51	2	68.0	4060	280	16240	1120	390