

ENDURO MULTISPIRAL HOSE

ENDURO5000

ENDURO ST COVER - FOUR SPIRAL WIRE HOSE
SPIRALLED WIRE REINFORCED HOSE - SAE 100
R13 - MILLION IMPULSE CYCLES

- Comes with SuperTuff (ST) cover for increased protection against abrasion in severe operating environments
- Recommended for: Extremely high pressure and high impulse hydraulic applications.
- Internal tube: Synthetic rubber, resistant against hydraulic fluids (HL, HLP, HLPD, HVLP, HFA, HFAS, HFB,HFC) and bio-degradable hydraulic fluids.
- Reinforcement: Four (six for -32) alternating layers of spiralled, high tensile steel wires.
- External cover: Weather & abrasion resistant synthetic rubber. MSHA approved.
- Temperature range: -40°C to +121°C
- Standards: ISO 18752-CC Exceeds SAE 100 R13.
- Characteristics: Extra flexible, up to 1/2 SAE bend radius



Part Number	Internal Size	Internal Diameter - DN	Internal Diameter - Inches	External Diameter - mm	Working Pressure - psi	Working pressure - bar	Min burst pressure - psi	Min burst pressure - bar	Min bend radius - mm
ENDURO50 00-06	06	10		20.2	5510	380	22040	1520	65
ENDURO50 00-08	08	12		22.9	5510	380	22040	1520	90
ENDURO50 00-10	10	16		26.5	5510	380	22040	1520	100
ENDURO50 00-12	12	19		30.5	5510	380	22040	1520	120
ENDURO50 00-16	16	25	1	37.9	5075	350	20300	1400	150
ENDURO50 00-20	20	32		45.9	5075	350	20300	1400	210
ENDURO50 00-24	24	38		53.4	5075	350	20300	1400	250
ENDURO50 00-32	32	51	2	71.5	5075	350	20300	1400	540