Hydraulink

MULTIPURPOSE HOSE

PREMOFLEX

Premoflex MULTI-PURPOSE HOSE
TWO YARN SPIRAL REINFORCED INDUSTRIAL HOSE



- Recommended for: Premo Flex is the perfect choice for multiple applications requiring a highly flexible and cost-effective hose with maximum resistance to petroleum oils/kerosene/fuel oil (to 120°F) and lubricating oils (to 212°F). Premo Flex can be used for transferring gasoline or diesel fuels. It is also suitable for air and water applications; It offers excellent weather and ozone resistance and is nonconductive at 1000 volts D.C.
- Temperature range: -40°F to +212°F(-40°C to +100°C) continuous service.
- Tube: Type C (Nitrile). Black. RMA (Class A) high oil resistance.
- Reinforcement: Synthetic high tensile cord.
- Cover: Type C2 (Modified Nitrile). Red (black cover available on special order). All sizes thru 1/2 are perforated. RMA(Class B) medium oil resistance.

Part Number	Internal Size	Internal Size (mm)	External Diameter (in)	External Diameter (mm)	Working Pressure (psi)	Working pressure (bar)	Min burst pressure (psi)	Min burst pressure (bar)	Min. bend radius (in)
PREMOFLEX-04	04	6.4	.5	12.7	250	17	750	52	2
PREMOFLEX-06	06	9.5	.66	16.8	250	17	750	52	3
PREMOFLEX-08	08	12.7	.85	21.6	250	17	750	52	4
PREMOFLEX-10	10	15.8	1	25.4	250	17	750	52	5
PREMOFLEX-12	12	19.1	1.15	29.2	250	17	750	52	5
PREMOFLEX-16	16	25.4	1.47	37.3	250	17	750	52	8

Please contact Hydraulink for further details and availability. Hydraulink reserve the right to change technical specifications without notice.