


## BSP

### S15

#### BSP TAPER MALE STRAIGHT



| Part Number | BSPT Male Thread - F | Hose I.D (in) | Hose I.D (mm) | Dash size | Hex A/F - S (mm) | Cutoff - H (mm) | Length - L (mm) | Working Pressure (bar) | Working Pressure (psi) |
|-------------|----------------------|---------------|---------------|-----------|------------------|-----------------|-----------------|------------------------|------------------------|
| S15-0204    | 1/8-28               | 1/4           | 6.4           | 04        | 12               | 21              | 49              | 350                    | 5000                   |
| S15-0404    | 1/4-19               | 1/4           | 6.4           | 04        | 15               | 25              | 53              | 350                    | 5000                   |
| S15-0406    | 1/4-19               | 3/8           | 9.5           | 06        | 15               | 26              | 56              | 350                    | 5000                   |
| S15-0408    | 1/4-19               | 1/2           | 12.7          | 08        | 22               | 29              | 62              | 350                    | 5000                   |
| S15-0604    | 3/8-19               | 1/4           | 6.4           | 04        | 19               | 26              | 54              | 280                    | 4000                   |
| S15-0605    | 3/8-19               | 5/16          | 7.9           | 05        | 19               | 26              | 54              | 280                    | 4000                   |
| S15-0606    | 3/8-19               | 3/8           | 9.5           | 06        | 19               | 27              | 57              | 280                    | 4000                   |
| S15-0608    | 3/8-19               | 1/2           | 12.7          | 08        | 19               | 28              | 64              | 280                    | 4000                   |
| S15-0806    | 1/2-14               | 3/8           | 9.5           | 06        | 22               | 32              | 63              | 280                    | 4000                   |
| S15-0808    | 1/2-14               | 1/2           | 12.7          | 08        | 22               | 33              | 66              | 280                    | 4000                   |
| S15-0812    | 1/2-14               | 3/4           | 19            | 12        | 27               | 38              | 78              | 280                    | 4000                   |
| S15-1010    | 5/8-14               | 5/8           | 15.9          | 10        | 25               | 35              | 72              | 280                    | 4000                   |
| S15-1208    | 3/4-14               | 1/2           | 12.7          | 08        | 27               | 36              | 68              | 280                    | 4000                   |
| S15-1210    | 3/4-14               | 5/8           | 15.9          | 10        | 27               | 35              | 71              | 280                    | 4000                   |
| S15-1212    | 3/4-14               | 3/4           | 19            | 12        | 27               | 36              | 77              | 280                    | 4000                   |
| S15-1216    | 3/4-14               | 1             | 25.4          | 16        | 32               | 42              | 98              | 280                    | 4000                   |
| S15-1612    | 1-11                 | 3/4           | 19            | 12        | 36               | 41              | 82              | 280                    | 4000                   |
| S15-1616    | 1-11                 | 1             | 25.4          | 16        | 36               | 44              | 101             | 280                    | 4000                   |
| S15-1620    | 1-11                 | 1 1/4         | 31.8          | 20        | 41               | 52              | 118             | 280                    | 4000                   |
| S15-2016    | 1 1/4-11             | 1             | 25.4          | 16        | 48               | 52              | 108             | 210                    | 3000                   |
| S15-2020    | 1 1/4-11             | 1 1/4         | 31.8          | 20        | 46               | 51              | 118             | 210                    | 3000                   |
| S15-2424    | 1 1/2-11             | 1 1/2         | 38            | 24        | 50               | 54              | 137             | 185                    | 2700                   |
| S15-3232    | 2-11                 | 2             | 51            | 32        | 65               | 64              | 160             | 175                    | 2500                   |